



# Certificate of Compliance & Material Safety Data Sheet

For Health Emergencies: CALL A POISON CONTROL CENTER  
For Transportation Emergencies ONLY: Call Chem-Tel  
USA, Canada, Puerto Rico, US Virgin Islands: Call 800-255-3924  
Outside North America: Call Collect 813-248-0585

Date Prepared  
Rev: 19 October 2011  
Replaces: 25 April 2011

---

## Certificate of Compliance Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: [Cleaning Solution for Paintings](#)

1.2 ITEM NUMBER AND SIZES: 1411 - 118ml, 1412 - 236ml, 1413 - 473ml

1.3 CPSC SAFETY REGULATION CITATION

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Poison Prevention Packaging Act, the Federal Hazardous Substances Act, (FHSA) and its Labeling for Hazardous Art Materials Amendment, (LHAMA.)

1.4 MANUFACTURER IDENTIFICATION:

Martin/F. Weber Co.  
2727 Southampton Road • Philadelphia, PA 19154 USA  
Phone: 215-677-5600 • Fax: 215-677-3336  
Email: [compliance@weberart.com](mailto:compliance@weberart.com) • Web: [www.weberart.com](http://www.weberart.com)

1.5 CONTACT INFORMATION:

Regulatory & Compliance Manager  
Martin/F. Weber Co.  
2727 Southampton Road • Philadelphia, PA 19154 USA  
Phone: 215-677-5600 • Fax: 215-677-3336  
Email: [compliance@weberart.com](mailto:compliance@weberart.com)

1.6 DATE & PLACE OF MANUFACTURE:

For purposes of the Consumer Product Safety Improvement Act, (CPSIA), this product is deemed to be manufactured as of the date of shipment, at the above address.

1.7 DATE & PLACE PRODUCT TESTED FOR COMPLIANCE WITH THE REGULATIONS ABOVE (1.4):

Date: 18 October 2011  
Place: Duke University Medical Center  
2200 West Main Street, Suite 400  
Durham NC 27705

1.8 THIRD-PARTY LABORATORY(S) ON WHICH THIS CERTIFICATE DEPENDS

N/A

---

## MSDS Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: [Cleaning Solution](#)

1.2 ITEM NUMBER AND SIZES: [1411 - 118ml, 1412 - 236ml, 1413 - 473ml](#)

1.3 COMPANY IDENTIFICATION:

[Martin/F. Weber Co.](#)  
[2727 Southampton Road • Philadelphia, PA 19154 USA](#)  
[Phone: 215-677-5600 • Fax: 215-677-3336](#)  
[Email: \[compliance@weberart.com\]\(mailto:compliance@weberart.com\) • Web: \[www.weberart.com\]\(http://www.weberart.com\)](#)

---

## SECTION 2 – COMPOSITION INFORMATION

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
<a href="#">Pure Gum Spirits of Turpentine</a>	<a href="#">9005-90-7</a>	<a href="#">36</a>
<a href="#">Petroleum Distillate</a>	<a href="#">64742-94-5</a>	<a href="#">33</a>
<a href="#">Denatured Ethyl Alcohol</a>	<a href="#">64-17-5</a>	<a href="#">33</a>

---

## SECTION 3 – HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

**Appearance:** [Clear to light yellow liquid](#)

**Physical State:** [Liquid](#)

**Odor:** [Typical pine derivative or turpentine odor](#)

**Hazards of Product:** [Flammable, Harmful or Fatal if Swallowed. Vapor Harmful. Skin and Eye Irritant](#)

3.2 POTENTIAL HEALTH EFFECTS

EFFECTS OF SINGLE ACUTE OVEREXPOSURE:

[Ingestion: Acute oral poisoning, nausea, vomiting, lack of coordination and coma. Inhalation: Headaches, nausea, confusion or instability. Skin or Eye Contact: Irritation and damage to affected area.](#)

CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE:

[Repeated or prolonged skin contact may produce skin irritation, dermatitis or chemical burns. Eye contact with liquid or vapor is irritating and damaging. Overexposure to vapors may produce headaches, nausea, confusion or instability. Repeated dermal or inhalation overexposure may produce kidney or bladder damage. Exposure may cause allergic reactions or harm to the developing fetus.](#)

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: [Liver, Kidney or Bladder conditions.](#)

3.3 POTENTIAL ENVIRONMENTAL EFFECTS: [n/a](#)

---

## SECTION 4 – FIRST AID PROCEDURES

4.1 INHALATION: [Move to fresh air. Get prompt medical attention.](#)

4.2 EYE CONTACT: [Wash eyes with tap water for five to ten \(5 – 10\) minutes. If irritation persists, seek prompt medical attention.](#)

4.3 SKIN CONTACT: Wash affected area with soap and water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.

4.4 SWALLOWING: If swallowed, do not induce vomiting. Call a physician or Poison Control Center immediately. Get prompt medical attention.

4.2 NOTES TO PHYSICIAN: n/a

---

## SECTION 5 - FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

<b>Identification Number:</b>	UN 1263
<b>Flash Point – Closed Cup:</b>	51°F (11°C)
<b>Flash Point – Open Cup:</b>	n/a
<b>Auto-Ignition Temperature:</b>	n/a
<b>Flammable Limits in Air:</b>	n/a

5.2 EXTINGUISHING MEDIA                      Foam, CO<sub>2</sub>, Dry Chemical (Class B) or Halon®

5.3 EXTINGUISHING MEDIA  
TO AVOID    Water

5.4 SPECIAL FIRE FIGHTING  
PROCEDURES                                        n/a

5.5 SPECIAL PROTECTIVE  
EQUIPMENT FOR FIREFIGHTERS              As with any fire situation, full face, self contained breathing apparatus and appropriate protective clothing should be worn.

5.6 UNUSUAL FIRE AND  
EXPLOSION HAZARDS                            n/a

5.7 HAZARDOUS COMBUSTION  
PRODUCTS                                        Under fire conditions, this product may release CO, CO<sub>2</sub>, and other decomposition products of undetermined hazard.

---

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep sources of ignition away. Small quantities may be cleaned up with rags or paper towels and transferred to airtight containers for disposal. Rags or paper towels soaked with this material should be placed in approved waste cans and / or soaked with water, for disposal in accordance with local state and federal regulations.

---

## SECTION 7 – HANDLING AND STORAGE

7.1 GENERAL HANDLING: Avoid ingestion. Avoid breathing vapors. Use exhaust fan to remove vapors and assure adequate ventilation. Do not transfer contents to unlabeled containers. KEEP OUT OF THE REACH OF CHILDREN. Keep from sources of ignition, oxidizing materials, heat and flame. KEEP AWAY FROM OPEN FLAMES. NO SMOKING in areas of use or storage.

7.2 STORAGE: Keep from sources of ignition, oxidizing materials, heat and flame. Keep containers closed when not in use.

---

## SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 EXPOSURE LIMITS:	100 PPM ACGIH TLV
8.2 PERSONAL PROTECTION:	
<b>Respiratory Protection:</b>	If TLV is exceeded, MSHA / NIOSH approved organic vapor respiratory protection should be worn.
<b>Ventilation:</b>	Use exhaust fan to remove vapors and assure adequate ventilation.
<b>Eye Protection:</b>	Use OSHA approved chemical splash goggles with side shields
<b>Protective Gloves:</b>	Neoprene or rubber – impervious gloves
<b>Other Protective Equipment:</b>	Body protection suitable for the work environment
8.3 ENGINEERING CONTROLS:	n/a

---

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	Clear to light yellow liquid
<b>pH:</b>	n/a
<b>Solubility in Water (by weight):</b>	Negligible
<b>Odor:</b>	Typical pine derivative or turpentine odor
<b>Flash Point – Closed Cup:</b>	51°F (11°C)
<b>Flash Point – Open Cup:</b>	n/a
<b>Percent Volatiles:</b>	99%
<b>Boiling Point (760mm Hg):</b>	275°F (135°C)
<b>Freezing Point:</b>	n/a
<b>Specific Gravity (H<sub>2</sub>O = 1):</b>	0.85
<b>Vapor Pressure at 20°C:</b>	4.5mg Hg
<b>Vapor Density (air = 1):</b>	3.8
<b>Evaporation Rate (Butyl Acetate = 1):</b>	<1
<b>Melting Point:</b>	n/a

---

## Section 10 – STABILITY AND REACTIVITY

10.1 STABILITY / INSTABILITY	Stable under ordinary conditions of use and storage
<b>Conditions to Avoid</b>	Keep from heat, open flame and sources of ignition
<b>Incompatible Materials</b>	Strong oxidizing agents, acids or acidic materials. Do not store in plastic containers.
10.2 HAZARDOUS POLYMERIZATION	May occur from contamination with strong acids.
10.3 INHIBITORS / STABILIZERS	n/a

---

## SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: **FLAMMABLE**. Harmful or fatal if swallowed. Vapor harmful. Eye and skin irritant. Overexposure may result in nausea, headache, confusion or instability.

CHRONIC TOXICITY: Exposure may cause allergic reactions or harm to the developing fetus. Overexposure may result in nausea, headache, confusion or instability.

---

## SECTION 12 – ECOLOGICAL INFORMATION

12.1 ENVIRONMENTAL FATE	n/a
12.2 ECOTOXICITY	n/a
12.3 FURTHER INFORMATION	n/a

---

## SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 WASTE DISPOSAL METHOD	Dispose of in accordance with local, state and federal regulations
13.2 DISPOSAL CONSIDERATIONS	Keep from heat, open flame, sparks and sources of ignition

---

## SECTION 14 – TRANSPORTATION INFORMATION

U.S. D.O.T	Domestic Ground: ORM-D Consumer Commodity Ocean Freight: UN 1263 Paint Related Material, Class 3 PG II, Limited Quantity Air Freight: DO NOT SHIP via air without special packaging and labeling. Contact your air carrier for detailed instructions
------------	--

---

## SECTION 15 – REGULATORY INFORMATION

15.1 FEDERAL / NATIONAL	n/a
15.2 STATE / LOCAL	n/a

---

## SECTION 16 – OTHER INFORMATION

HMIS® Ratings:	Health=2 Flammability=3 Physical Hazard=0
----------------	---

The information presented here is current as of the date of this Material Safety Data Sheet and is believed to be accurate but is not warranted to be, whether originating with the company or not. Since use of this information and the product are not under the control of Martin/F. Weber Company, it is the user's obligation to determine conditions of safe use, in advance of use, and to carefully read the product label and follow all instructions for safe use of the product.

HMIS® is a registered trade mark of the American Coatings Association